97TH GENERAL ASSEMBLY

State of Illinois

2011 and 2012

HB4446

Introduced 1/30/2012, by Rep. David Reis

SYNOPSIS AS INTRODUCED:

625 ILCS 5/15-107

from Ch. 95 1/2, par. 15-107

Amends the Illinois Vehicle Code. Provides that the length limits for the distance between the kingpin and the center of the rear axle of semitrailers longer than 48 feet shall not apply to trailers used for the transport of livestock.

LRB097 15671 HEP 60813 b

1

AN ACT concerning transportation.

2 Be it enacted by the People of the State of Illinois, 3 represented in the General Assembly:

Section 5. The Illinois Vehicle Code is amended by changing
Section 15-107 as follows:

6 (625 ILCS 5/15-107) (from Ch. 95 1/2, par. 15-107)
7 Sec. 15-107. Length of vehicles.

8 (a) The maximum length of a single vehicle on any highway9 of this State may not exceed 42 feet except the following:

10

(1) Semitrailers.

(2) Charter or regulated route buses may be up to 45
 feet in length, not including energy absorbing bumpers.

(a-1) A motor home as defined in Section 1-145.01 may be up
to 45 feet in length, not including energy absorbing bumpers.
The length limitations described in this subsection (a-1) shall
be exclusive of energy-absorbing bumpers and rear view mirrors.

17 (b) On all non-State highways, the maximum length of 18 vehicles in combinations is as follows:

19 (1) A truck tractor in combination with a semitrailer
 20 may not exceed 55 feet overall dimension.

(2) A truck tractor-semitrailer-trailer or truck
 tractor semitrailer-semitrailer may not exceed 60 feet
 overall dimension.

(3) Combinations specially designed to transport motor 1 2 vehicles or boats may not exceed 60 feet overall dimension. Vehicles operating during daylight hours when transporting 3 poles, pipes, machinery, or other objects of a structural 4 5 nature that cannot readily be dismembered are exempt from length limitations, provided that no object may exceed 80 feet 6 in length and the overall dimension of the vehicle including 7 8 the load may not exceed 100 feet. This exemption does not apply 9 to operation on a Saturday, Sunday, or legal holiday. Legal 10 holidays referred to in this Section are the days on which the 11 following traditional holidays are celebrated: New Year's Day; 12 Memorial Day; Independence Day; Labor Day; Thanksgiving Day; 13 and Christmas Day.

Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided that during night operations every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps on the extreme ends of any projecting load to clearly mark the dimensions of the load.

A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.

All other combinations not listed in this subsection (b)may not exceed 60 feet overall dimension.

(c) Except as provided in subsections (c-1) and (c-2), 1 2 combinations of vehicles may not exceed a total of 2 vehicles 3 except the following: (1) A truck tractor semitrailer may draw one trailer. 4 5 (2) A truck tractor semitrailer may draw one converter 6 dolly or one semitrailer. 7 (3) A truck tractor semitrailer may draw one vehicle 8 that is defined in Chapter 1 as special mobile equipment, 9 provided the overall dimension does not exceed 60 feet. 10 (4) A truck in transit may draw 3 trucks in transit 11 coupled together by the triple saddlemount method. 12 (5) Recreational vehicles consisting of 3 vehicles, 13 provided the following: (A) The total overall dimension does not exceed 60 14 feet. 15 16 (B) The towing vehicle is a properly registered 17 vehicle capable of towing another vehicle using a fifth-wheel type assembly. 18 The second vehicle in the combination of 19 (C) 20 vehicles is a recreational vehicle that is towed by a 21 fifth-wheel assembly. This vehicle must be properly 22 registered and must be equipped with brakes, 23 regardless of weight. (D) The third vehicle must be the lightest of the 3 24 25 vehicles and be a trailer or semitrailer designed or 26 used for transporting a boat, all-terrain vehicle,

HB4446

- 3 - LRB097 15671 HEP 60813 b

HB4446 - 4 - LRB097 15671 HEP 60813 b

1

2

3

personal watercraft, or motorcycle.

(E) The towed vehicles may be only for the use of the operator of the towing vehicle.

4 (F) All vehicles must be properly equipped with
5 operating brakes and safety equipment required by this
6 Code, except the additional brake requirement in
7 subdivision (C) of this subparagraph (5).

8 (6) A tow truck in combination with a disabled vehicle 9 or combination of disabled vehicles, provided the towing 10 vehicle:

11 (A) Is specifically designed as a tow truck having 12 a gross vehicle weight rating of at least 18,000 pounds and equipped with air brakes, provided that air brakes 13 14 are required only if the towing vehicle is towing a 15 vehicle, semitrailer, or tractor-trailer combination 16 that is equipped with air brakes. For the purpose of 17 this subsection, gross vehicle weight rating, or GVWR, means the value specified by the manufacturer as the 18 19 loaded weight of the tow truck.

20 (B) Is equipped with flashing, rotating, or 21 oscillating amber lights, visible for at least 500 feet 22 in all directions.

(C) Is capable of utilizing the lighting and
braking systems of the disabled vehicle or combination
of vehicles.

26

(D) Does not engage a tow exceeding 50 highway

- 5 - LRB097 15671 HEP 60813 b

miles from the initial point of wreck or disablement to a place of repair. Any additional movement of the vehicles may occur only upon issuance of authorization for that movement under the provisions of Sections 15-301 through 15-319 of this Code.

6 The Department may by rule or regulation prescribe 7 additional requirements regarding length limitations for a 8 tow truck towing another vehicle.

9 For purposes of this Section, a tow-dolly that merely 10 serves as substitute wheels for another legally licensed 11 vehicle is considered part of the licensed vehicle and not 12 a separate vehicle.

13 (7) Commercial vehicles consisting of 3 vehicles,14 provided the following:

15 (A) The total overall dimension does not exceed 6516 feet.

(B) The towing vehicle is a properly registered
vehicle capable of towing another vehicle using a
fifth-wheel type assembly or a goose-neck hitch ball.

20 (C) The third vehicle must be the lightest of the 3
21 vehicles and be a trailer or semitrailer.

(D) All vehicles must be properly equipped with
 operating brakes and safety equipment required by this
 Code.

(E) The combination of vehicles must be operated by
a person who holds a commercial driver's license (CDL).

```
HB4446
```

- 6 - LRB097 15671 HEP 60813 b

(F) The combination of vehicles must be en route to 1 a location where new or used trailers are sold by an 2 Illinois or out-of-state licensed new or used trailer 3 dealer. 4 5 (c-1) A combination of 3 vehicles is allowed access to any 6 State designated highway if: 7 (1) the length of neither towed vehicle exceeds 28.5 8 feet; 9 (2) the overall wheel base of the combination of 10 vehicles does not exceed 62 feet; and 11 (3) the combination of vehicles is en route to a 12 location where new or used trailers are sold by an Illinois 13 or out-of-state licensed new or used trailer dealer. (c-2) A combination of 3 vehicles is allowed access from 14 15 any State designated highway onto any county, township, or 16 municipal highway for a distance of 5 highway miles for the 17 purpose of delivery or collection of one or both of the towed vehicles if: 18 (1) the length of neither towed vehicle exceeds 28.5 19 feet; 20 (2) the combination of vehicles does not exceed 40,000 21 22 pounds in gross weight and 8 feet 6 inches in width; 23 (3) there is no sign prohibiting that access; 24 (4) the route is not being used as a thoroughfare 25 between State designated highways; and (5) the combination of vehicles is en route to a 26

1 2 location where new or used trailers are sold by an Illinois or out-of-state licensed new or used trailer dealer.

3 (d) On Class I highways there are no overall length 4 limitations on motor vehicles operating in combinations 5 provided:

6

7

(1) The length of a semitrailer, unladen or with load, in combination with a truck tractor may not exceed 53 feet.

8 (2) The distance between the kingpin and the center of 9 the rear axle of a semitrailer longer than 48 feet, in 10 combination with a truck tractor, may not exceed 45 feet 6 11 inches. <u>The length limit contained in this paragraph (2)</u> 12 <u>shall not apply to trailers used for the transport of</u> 13 <u>livestock.</u>

14 (3) The length of a semitrailer or trailer, unladen or 15 with load, operated in a truck tractor-semitrailer-trailer 16 or truck tractor semitrailer-semitrailer combination, may 17 not exceed 28 feet 6 inches.

18 (4) Maxi-cube combinations, as defined in Chapter 1,
19 may not exceed 65 feet overall dimension.

(5) Combinations of vehicles specifically designed to
transport motor vehicles or boats may not exceed 65 feet
overall dimension. The length limitation is inclusive of
front and rear bumpers but exclusive of the overhang of the
transported vehicles, as provided in paragraph (i) of this
Section.

26

(6) Stinger steered semitrailer vehicles as defined in

Chapter 1, specifically designed to transport motor 1 2 vehicles or boats, may not exceed 75 feet overall dimension. The length limitation is inclusive of front and 3 bumpers but exclusive of the overhang of 4 rear the 5 transported vehicles, as provided in paragraph (i) of this 6 Section.

7 (7) A truck in transit transporting 3 trucks coupled
8 together by the triple saddlemount method may not exceed 75
9 feet overall dimension.

10 Vehicles operating during daylight hours when transporting 11 poles, pipes, machinery, or other objects of a structural 12 nature that cannot readily be dismembered are exempt from length limitations, provided that no object may exceed 80 feet 13 in length and the overall dimension of the vehicle including 14 the load may not exceed 100 feet. This exemption does not apply 15 16 to operation on a Saturday, Sunday, or legal holiday. Legal 17 holidays referred to in this Section are the days on which the following traditional holidays are celebrated: New Year's Day; 18 19 Memorial Day; Independence Day; Labor Day; Thanksgiving Day; 20 and Christmas Day.

Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided that during night operations every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps on the extreme ends of any projecting

HB4446 - 9 - LRB097 15671 HEP 60813 b

1 load to clearly mark the dimensions of the load.

A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.

6 The length limitations described in this paragraph (d) 7 shall be exclusive of safety and energy conservation devices, 8 such as bumpers, refrigeration units or air compressors and 9 other devices, that the Department may interpret as necessary 10 for safe and efficient operation; except that no device 11 excluded under this paragraph shall have by its design or use 12 the capability to carry cargo.

Section 5-35 of the Illinois Administrative Procedure Act relating to procedures for rulemaking shall not apply to the designation of highways under this paragraph (d).

16 (e) On Class II highways there are no overall length 17 limitations on motor vehicles operating in combinations, 18 provided:

(1) The length of a semitrailer, unladen or with load,
in combination with a truck tractor, may not exceed 53 feet
overall dimension.

(2) The distance between the kingpin and the center of
the rear axle of a semitrailer longer than 48 feet, in
combination with a truck tractor, may not exceed 45 feet 6
inches. <u>The length limit contained in this paragraph (2)</u>
shall not apply to trailers used for the transport of

1

livestock.

2 (3) A truck tractor-semitrailer-trailer or truck
3 tractor semitrailer-semitrailer combination may not exceed
4 65 feet in dimension from front axle to rear axle.

5 (4) The length of a semitrailer or trailer, unladen or 6 with load, operated in a truck tractor-semitrailer-trailer 7 or truck tractor semitrailer-semitrailer combination, may 8 not exceed 28 feet 6 inches.

9 (5) Maxi-cube combinations, as defined in Chapter 1, 10 may not exceed 65 feet overall dimension.

(6) A combination of vehicles, specifically designed to transport motor vehicles or boats, may not exceed 65 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.

(7) Stinger steered semitrailer vehicles, as defined
in Chapter 1, specifically designed to transport motor
vehicles or boats, may not exceed 75 feet overall
dimension. The length limitation is inclusive of front and
rear bumpers but exclusive of the overhang of the
transported vehicles, as provided in paragraph (i) of this
Section.

(8) A truck in transit transporting 3 trucks coupled
together by the triple saddlemount method may not exceed 75
feet overall dimension.

- 11 - LRB097 15671 HEP 60813 b

Vehicles operating during daylight hours when transporting 1 2 poles, pipes, machinery, or other objects of a structural nature that cannot readily be dismembered are exempt from 3 length limitations, provided that no object may exceed 80 feet 4 5 in length and the overall dimension of the vehicle including the load may not exceed 100 feet. This exemption does not apply 6 to operation on a Saturday, Sunday, or legal holiday. Legal 7 8 holidays referred to in this Section are the days on which the 9 following traditional holidays are celebrated: New Year's Day; 10 Memorial Day; Independence Day; Labor Day; Thanksgiving Day; 11 and Christmas Day.

Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided that during night operations every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps on the extreme ends of any projecting load to clearly mark the dimensions of the load.

A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.

Local authorities, with respect to streets and highways under their jurisdiction, may also by ordinance or resolution allow length limitations of this subsection (e).

26 The length limitations described in this paragraph (e)

HB4446

1 shall be exclusive of safety and energy conservation devices, 2 such as bumpers, refrigeration units or air compressors and 3 other devices, that the Department may interpret as necessary 4 for safe and efficient operation; except that no device 5 excluded under this paragraph shall have by its design or use 6 the capability to carry cargo.

Section 5-35 of the Illinois Administrative Procedure Act relating to procedures for rulemaking shall not apply to the designation of highways under this paragraph (e).

10 (e-1) Combinations of vehicles not exceeding 65 feet 11 overall length are allowed access as follows:

(1) From any State designated highway onto any county,
township, or municipal highway for a distance of 5 highway
miles for the purpose of loading and unloading, provided:

(A) The vehicle does not exceed 80,000 pounds in
 gross weight and 8 feet 6 inches in width.

(B) There is no sign prohibiting that access.

18 (C) The route is not being used as a thoroughfare19 between State designated highways.

(2) From any State designated highway onto any county
or township highway for a distance of 5 highway miles or
onto any municipal highway for a distance of one highway
mile for the purpose of food, fuel, repairs, and rest,
provided:

(A) The vehicle does not exceed 80,000 pounds in
 gross weight and 8 feet 6 inches in width.

17

1

(B) There is no sign prohibiting that access.

2 (C) The route is not being used as a thoroughfare3 between State designated highways.

4 (e-2) Except as provided in subsection (e-3), combinations 5 of vehicles over 65 feet in length, with no overall length 6 limitation except as provided in subsections (d) and (e) of 7 this Section, are allowed access as follows:

8 (1) From a Class I highway onto any street or highway 9 for a distance of one highway mile for the purpose of 10 loading, unloading, food, fuel, repairs, and rest, 11 provided there is no sign prohibiting that access.

12 (2) From a Class I or Class II highway onto any State
13 highway or any locally designated highway for a distance of
14 5 highway miles for the purpose of loading, unloading,
15 food, fuel, repairs, and rest.

16 (e-3) Combinations of vehicles over 65 feet in length 17 operated by household goods carriers, with no overall length 18 limitations except as provided in subsections (d) and (e) of 19 this Section, have unlimited access to points of loading and 20 unloading.

(f) On Class III and other non-designated State highways, the length limitations for vehicles in combination are as follows:

(1) Truck tractor-semitrailer combinations, must
 comply with either a maximum 55 feet overall wheel base or
 a maximum 65 feet extreme overall dimension.

(2) Semitrailers, unladen or with load, may not exceed
 53 feet overall dimension.

3 (3) No truck tractor-semitrailer-trailer or truck
4 tractor semitrailer-semitrailer combination may exceed 60
5 feet extreme overall dimension.

6 (4) The distance between the kingpin and the center 7 axle of a semitrailer longer than 48 feet, in combination 8 with a truck tractor, may not exceed 42 feet 6 inches. <u>The</u> 9 <u>length limit contained in this paragraph (4) shall not</u> 10 <u>apply to trailers used for the transport of livestock.</u>

(g) Length limitations in the preceding subsections of this
 Section 15-107 do not apply to the following:

13 (1) Vehicles operated in the daytime, except on 14 Saturdays, Sundays, or legal holidays, when transporting 15 poles, pipe, machinery, or other objects of a structural 16 nature that cannot readily be dismembered, provided the 17 overall length of vehicle and load may not exceed 100 feet no object exceeding 80 feet in 18 length may be and 19 transported unless a permit has been obtained as authorized in Section 15-301. 20

(2) Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties, but during night operation every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps upon the extreme ends of any projecting load to clearly

1 mark the dimensions of the load.

2 (3) A tow truck in combination with a disabled vehicle
3 or combination of disabled vehicles, provided the towing
4 vehicle meets the following conditions:

5 (A) It is specifically designed as a tow truck 6 having a gross vehicle weight rating of at least 18,000 7 pounds and equipped with air brakes, provided that air 8 brakes are required only if the towing vehicle is 9 towing a vehicle, semitrailer, or tractor-trailer 10 combination that is equipped with air brakes.

(B) It is equipped with flashing, rotating, or
oscillating amber lights, visible for at least 500 feet
in all directions.

14 (C) It is capable of utilizing the lighting and
15 braking systems of the disabled vehicle or combination
16 of vehicles.

17 (D) It does not engage in a tow exceeding 50 miles
18 from the initial point of wreck or disablement.

19 The Department may by rule or regulation prescribe 20 additional requirements regarding length limitations for a tow 21 truck towing another vehicle. The towing vehicle, however, may 22 tow any disabled vehicle from the initial point of wreck or 23 disablement to a point where repairs are actually to occur. 24 This movement shall be valid only on State routes. The tower 25 must abide by posted bridge weight limits.

26 For the purpose of this subsection, gross vehicle weight

1 rating, or GVWR, shall mean the value specified by the 2 manufacturer as the loaded weight of the tow truck. Legal 3 holidays referred to in this Section shall be specified as the 4 day on which the following traditional holidays are celebrated: 5 New Year's Day;

6 Memorial Day;

7 Independence Day;

8 Labor Day;

9 Thanksgiving Day; and

10 Christmas Day.

11 (h) The load upon any vehicle operated alone, or the load 12 upon the front vehicle of a combination of vehicles, shall not 13 extend more than 3 feet beyond the front wheels of the vehicle 14 or the front bumper of the vehicle if it is equipped with a 15 front bumper. The provisions of this subsection (h) shall not 16 apply to any vehicle or combination of vehicles specifically 17 designed for the collection and transportation of waste, recyclable materials during the 18 garbage, or vehicle's 19 operation in the course of collecting garbage, waste, or 20 recyclable materials if the vehicle is traveling at a speed not in excess of 15 miles per hour during the vehicle's operation 21 22 and in the course of collecting garbage, waste, or recyclable 23 materials. However, in no instance shall the load extend more than 7 feet beyond the front wheels of the vehicle or the front 24 25 bumper of the vehicle if it is equipped with a front bumper.

26 (i) The load upon the front vehicle of a combination of

HB4446

vehicles specifically designed to transport motor vehicles shall not extend more than 3 feet beyond the foremost part of the transporting vehicle and the load upon the rear transporting vehicle shall not extend more than 4 feet beyond the rear of the bed or body of the vehicle. This paragraph shall only be applicable upon highways designated in paragraphs (d) and (e) of this Section.

8 (j) Articulated vehicles comprised of 2 sections, neither 9 of which exceeds a length of 42 feet, designed for the carrying 10 of more than 10 persons, may be up to 60 feet in length, not 11 including energy absorbing bumpers, provided that the vehicles 12 are:

operated by or for any public body or motor carrier
 authorized by law to provide public transportation
 services; or

operated in local public transportation service by
 any other person and the municipality in which the service
 is to be provided approved the operation of the vehicle.

19 (j-1) (Blank).

(k) Any person who is convicted of violating this Section
is subject to the penalty as provided in paragraph (b) of
Section 15-113.

23 (l) (Blank).

24 (Source: P.A. 96-34, eff. 1-1-10; 96-37, eff. 7-13-09; 96-1352,
25 eff. 7-28-10; 97-200, eff. 7-27-11.)

HB4446