

SB3090



101ST GENERAL ASSEMBLY

State of Illinois

2019 and 2020

SB3090

Introduced 2/6/2020, by Sen. Chapin Rose

SYNOPSIS AS INTRODUCED:

625 ILCS 5/12-803

from Ch. 95 1/2, par. 12-803

Amends the Illinois Vehicle Code. Provides that a school bus may be equipped with an extended stop signal or second stop signal apparatus on the driver's side of the school bus that: (1) extends no more than 7 feet from the school bus, (2) can break away from the original stop signal without affecting the operation of the original stop signal, and (3) includes a second octagonal sign that conforms to the same requirements as the original stop signal.

LRB101 17477 HEP 66887 b

A BILL FOR

1 AN ACT concerning transportation.

2 **Be it enacted by the People of the State of Illinois,**
3 **represented in the General Assembly:**

4 Section 5. The Illinois Vehicle Code is amended by changing
5 Section 12-803 as follows:

6 (625 ILCS 5/12-803) (from Ch. 95 1/2, par. 12-803)

7 Sec. 12-803. (a) Each school bus shall be equipped with a
8 stop signal arm on the driver's side of the school bus that may
9 be operated either manually or mechanically. For each school
10 bus manufactured on and after September 1, 1992, the stop
11 signal arm shall be an octagon shaped semaphore that conforms
12 to 49 C.F.R. 571.131, "SCHOOL BUS PEDESTRIAN SAFETY DEVICES",
13 S5.1 through S5.5.

14 (b) Each school bus manufactured prior to September 1, 1992
15 shall be equipped with a stop signal arm that conforms to
16 standards promulgated by the Department.

17 (c) A school bus may be equipped with an extended stop
18 signal or second stop signal apparatus on the driver's side of
19 the school bus that:

20 (1) extends no more than 7 feet from the school bus;

21 (2) is attached to the stop signal arm required under
22 subsection (a) so that, if the second stop signal apparatus
23 is struck by a vehicle, the second stop signal apparatus

1 separates from the school bus without affecting the
2 operation of the stop signal arm required under subsection
3 (a); and

4 (3) includes a second octagonal sign that conforms to
5 the same requirements as the octagon shaped semaphore
6 required under subsection (a).

7 (Source: P.A. 88-415.)