

93RD GENERAL ASSEMBLY State of Illinois 2003 and 2004 SB2343

Introduced 1/28/2004, by Sen. Frank C. Watson

SYNOPSIS AS INTRODUCED:

625 ILCS 5/15-111 from Ch. 95 1/2, par. 15-111 from Ch. 95 1/2, par. 15-201 from Ch. 95 1/2, par. 15-201 from Ch. 95 1/2, par. 15-202 from Ch. 95 1/2, par. 15-202 from Ch. 95 1/2, par. 15-202

Amends the Illinois Vehicle Code. Provides that a vehicle transporting agricultural cash crops or loads of fruits or vegetables on an interstate, designated, or non-designated highway, during the harvest season only, is in compliance with weight restrictions if its gross weight is less than 80,000 pounds and exceeds the permitted gross weight by not more than 10%and the vehicle is traveling from the field to the first point processing. Provides that the operator of the vehicle must abide by posted bridge weight limits. Provides that the State Police are prohibited from routinely stopping and weighing vehicles transporting a particular commodity or vehicles in a particular geographic location. Provides that the Department of State Police shall provide training and continuing education to State Police officers concerning the prohibition. Provides that, beginning January 1, 2005 and through December 31, 2005, a State Police officer issuing a citation for an alleged violation of the maximum weight limits of the Code must record the make and year of the vehicle stopped, the date and time of the stop, the county and location of the stop, the type of commodity being transported, the weight of the vehicle, and the amount, if any, by which the weight of the vehicle exceeds the permitted weight. Provides that the Department of State Police shall, by February 1, 2006, compile the required data. Provides that the Department of State Police, in cooperation with the Illinois Department of Agriculture, shall, by March 15, 2006, analyze the data and submit a report of the findings to the General Assembly. Effective immediately.

LRB093 20251 DRH 46017 b

FISCAL NOTE ACT
MAY APPLY

3

9

10

11

12

13

14

15

16

17

18

19

20

2.1

22

23

24

25

26

27

28

29

30

31

32

1 AN ACT concerning vehicles.

Be it enacted by the People of the State of Illinois, represented in the General Assembly:

- Section 5. The Illinois Vehicle Code is amended by changing Sections 15-111, 15-201, and 15-202 and by adding Section 15-202.1 as follows: as follows:
- 7 (625 ILCS 5/15-111) (from Ch. 95 1/2, par. 15-111)
- 8 Sec. 15-111. Wheel and axle loads and gross weights.
 - (a) On non-designated highways, no vehicle or combination of vehicles equipped with pneumatic tires may be operated, unladen or with load, when the total weight transmitted to the road surface exceeds 18,000 pounds on a single axle or 32,000 pounds on a tandem axle with no axle within the tandem exceeding 18,000 pounds except:
 - (1) when a different limit is established and posted in accordance with Section 15-316 of this Code;
 - (2) vehicles for which the Department of Transportation and local authorities issue overweight permits under authority of Section 15-301 of this Code;
 - (3) tow trucks subject to the conditions provided in subsection (d) may not exceed 24,000 pounds on a single rear axle or 44,000 pounds on a tandem rear axle;
 - (4) any single axle of a 2-axle truck weighing 36,000 pounds or less and not a part of a combination of vehicles, shall not exceed 20,000 pounds;
 - (5) any single axle of a 2-axle truck equipped with a personnel lift or digger derrick, weighing 36,000 pounds or less, owned and operated by a public utility, shall not exceed 20,000 pounds;
 - (6) any single axle of a 2-axle truck specially equipped with a front loading compactor used exclusively for garbage, refuse, or recycling may not exceed 20,000

pounds per axle, provided that the gross weight of the vehicle does not exceed 40,000 pounds;

- (7) a truck, not in combination and specially equipped with a selfcompactor or an industrial roll-off hoist and roll-off container, used exclusively for garbage or refuse operations may, when laden, transmit upon the road surface the following maximum weights: 22,000 pounds on a single axle; 40,000 pounds on a tandem axle;
- (8) a truck, not in combination and used exclusively for the collection of rendering materials, may, when laden, transmit upon the road surface the following maximum weights: 22,000 pounds on a single axle; 40,000 pounds on a tandem axle;
- (9) tandem axles on a 3-axle truck registered as a Special Hauling Vehicle, manufactured prior to or in the model year of 2014 and first registered in Illinois prior to January 1, 2015, with a distance greater than 72 inches but not more than 96 inches between any series of 2 axles, is allowed a combined weight on the series not to exceed 36,000 pounds and neither axle of the series may exceed 18,000 pounds. Any vehicle of this type manufactured after the model year of 2014 or first registered in Illinois after December 31, 2014 may not exceed a combined weight of 32,000 pounds through the series of 2 axles and neither axle of the series may exceed 18,000 pounds;
- (10) tandem axles on a 4-axle truck mixer, whose fourth axle is a road surface engaging mixer trailing axle, registered as a Special Hauling Vehicle, used exclusively for the mixing and transportation of concrete and manufactured prior to or in the model year of 2014 and first registered in Illinois prior to January 1, 2015, with a distance greater than 72 inches but not more than 96 inches between any series of 2 axles, is allowed a combined weight on the series not to exceed 36,000 pounds and neither axle of the series may exceed 18,000 pounds. Any vehicle of this type manufactured after the model year of

2014 or first registered in Illinois after December 31, 2014 may not exceed a combined weight of 32,000 pounds through the series of 2 axles and neither axle of the series may exceed 18,000 pounds;

(11) 4-axle vehicles or a 5 or more axle combination of vehicles: The weight transmitted upon the road surface through any series of 3 axles whose centers are more than 96 inches apart, measured between extreme axles in the series, may not exceed those allowed in the table contained in subsection (f) of this Section. No axle or tandem axle of the series may exceed the maximum weight permitted under this Section for a single or tandem axle.

No vehicle or combination of vehicles equipped with other than pneumatic tires may be operated, unladen or with load, upon the highways of this State when the gross weight on the road surface through any wheel exceeds 800 pounds per inch width of tire tread or when the gross weight on the road surface through any axle exceeds 16,000 pounds.

(b) On non-designated highways, the gross weight of vehicles and combination of vehicles including the weight of the vehicle or combination and its maximum load shall be subject to the foregoing limitations and further shall not exceed the following gross weights dependent upon the number of axles and distance between extreme axles of the vehicle or combination measured longitudinally to the nearest foot.

27		VEHICLES O	R COMBINATIONS		
28		HAVIN	G 3 AXLES		
29	With Tandem		With or		
30	Axles		Without		
31			Tandem Axles		
32	Minimum		Minimum		
33	distance to	Maximum	distance to	Maximum	
34	nearest foot	Gross	nearest foot	Gross	

_	4	_
---	---	---

1	between	Weight	between	Weight
2	extreme axles	(pounds)	extreme axles	(pounds)
3	10 feet	41,000	16 feet	46,000
4	11	42,000	17	47,000
5	12	43,000	18	47,500
6	13	44,000	19	48,000
7	14	44,500	20	49,000
8	15	45,000	21 feet or more	50,000
9	VEHICL:	ES OR COMBI	NATIONS HAVING 4 AXL	ES
10	Minimum		Minimum	
11	distance to	Maximum	distance to	Maximum
12	nearest foot	Gross	nearest foot	Gross
13	between	Weight	between	Weight
14	extreme axles	(pounds)	extreme axles	(pounds)
15	15 feet	50,000	26 feet	57,500
16	16	50,500	27	58,000
17	17	51,500	28	58,500
18	18	52,000	29	59,500
19	19	52,500	30	60,000
20	20	53,500	31	60,500
21	21	54,000	32	61,500
22	22	54,500	33	62,000
23	23	55,500	34	62,500
24	24	56,000	35	63,500
25	25	56,500	36 feet or more	64,000
26	A vehicle not i	in a combina	ation having more tha	an 4 axles may
27	not exceed the weigh	ght in the t	able in this subsect	cion (b) for 4

28 axles measured between the extreme axles of the vehicle.

29 COMBINATIONS HAVING 5 OR MORE AXLES

30	Minimum distance to	Maximum
31	nearest foot between	Gross Weight
32	extreme axles	(pounds)
33	42 feet or less	72,000
34	43	73,000
35	44 feet or more	73,280

1 VEHICLES OPERATING ON CRAWLER TYPE TRACKS 40,000 pounds

2	TRUCKS EQUIPPED WITH SELFCOMPACTORS
3	OR ROLL-OFF HOISTS AND ROLL-OFF CONTAINERS FOR GARBAGE
4	OR REFUSE HAULS ONLY AND TRUCKS USED FOR
5	THE COLLECTION OF RENDERING MATERIALS
6	On Highway Not Part of National System
7	of Interstate and Defense Highways
8	with 2 axles 36,000 pounds
9	with 3 axles 54,000 pounds
10	TWO AXLE TRUCKS EQUIPPED WITH
11	A FRONT LOADING COMPACTOR USED EXCLUSIVELY
12	FOR THE COLLECTION OF GARBAGE, REFUSE, OR RECYCLING
13	with 2 axles 40,000 pounds
14	(b-1) A vehicle transporting agricultural cash crops or
15	loads of fruits or vegetables on an interstate, designated, or
16	non-designated highway, during the harvest season only, is in
17	compliance with this Section if its gross weight is less than
18	80,000 pounds and exceeds the gross weight permitted by this
19	Section by not more than 10% and the vehicle is traveling from
20	the field to the first point of processing. The operator of the
21	vehicle, however, must abide by posted bridge weight limits.
22	(c) Cities having a population of more than 50,000 may
23	permit by ordinance axle loads on 2 axle motor vehicles 33 1/2%
24	above those provided for herein, but the increase shall not
25	become effective until the city has officially notified the
26	Department of the passage of the ordinance and shall not apply
27	to those vehicles when outside of the limits of the city, nor
28	shall the gross weight of any 2 axle motor vehicle operating
29	over any street of the city exceed 40,000 pounds.
30	(d) Weight limitations shall not apply to vehicles
31	(including loads) operated by a public utility when
32	transporting equipment required for emergency repair of public
33	utility facilities or properties or water wells.

A combination of vehicles, including a tow truck and a disabled vehicle or disabled combination of vehicles, that exceeds the weight restriction imposed by this Code, may be operated on a public highway in this State provided that neither the disabled vehicle nor any vehicle being towed nor the tow truck itself shall exceed the weight limitations permitted under this Chapter. During the towing operation, neither the tow truck nor the vehicle combination shall exceed 24,000 pounds on a single rear axle and 44,000 pounds on a tandem rear axle, provided the towing vehicle:

- (1) is specifically designed as a tow truck having a gross vehicle weight rating of at least 18,000 pounds and is equipped with air brakes, provided that air brakes are required only if the towing vehicle is towing a vehicle, semitrailer, or tractor-trailer combination that is equipped with air brakes;
- (2) is equipped with flashing, rotating, or oscillating amber lights, visible for at least 500 feet in all directions;
- (3) is capable of utilizing the lighting and braking systems of the disabled vehicle or combination of vehicles; and
- (4) does not engage in a tow exceeding 20 miles from the initial point of wreck or disablement. Any additional movement of the vehicles may occur only upon issuance of authorization for that movement under the provisions of Sections 15-301 through 15-319 of this Code.

Gross weight limits shall not apply to the combination of the tow truck and vehicles being towed. The tow truck license plate must cover the operating empty weight of the tow truck only. The weight of each vehicle being towed shall be covered by a valid license plate issued to the owner or operator of the vehicle being towed and displayed on that vehicle. If no valid plate issued to the owner or operator of that vehicle is displayed on that vehicle, or the plate displayed on that vehicle does not cover the weight of the vehicle, the weight of

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

the vehicle shall be covered by the third tow truck plate issued to the owner or operator of the tow truck and temporarily affixed to the vehicle being towed.

The Department may by rule or regulation prescribe additional requirements. However, nothing in this Code shall prohibit a tow truck under instructions of a police officer from legally clearing a disabled vehicle, that may be in violation of weight limitations of this Chapter, from the roadway to the berm or shoulder of the highway. If in the opinion of the police officer that location is unsafe, the officer is authorized to have the disabled vehicle towed to the nearest place of safety.

For the purpose of this subsection, gross vehicle weight rating, or GVWR, shall mean the value specified by the manufacturer as the loaded weight of the tow truck.

- (e) No vehicle or combination of vehicles equipped with pneumatic tires shall be operated, unladen or with load, upon the highways of this State in violation of the provisions of any permit issued under the provisions of Sections 15-301 through 15-319 of this Chapter.
- (f) On designated Class I, II, or III highways and the National System of Interstate and Defense Highways, no vehicle or combination of vehicles with pneumatic tires may be operated, unladen or with load, when the total weight on the road surface exceeds the following: 20,000 pounds on a single axle; 34,000 pounds on a tandem axle with no axle within the tandem exceeding 20,000 pounds; 80,000 pounds gross weight for vehicle combinations of 5 or more axles; or a total weight on a group of 2 or more consecutive axles in excess of that weight produced by the application of the following formula: W = 500times the sum of (LN divided by N-1) + 12N + 36, where "W" equals overall total weight on any group of 2 or more consecutive axles to the nearest 500 pounds, "L" equals the distance measured to the nearest foot between extremes of any group of 2 or more consecutive axles, and "N" equals the number of axles in the group under consideration.

2 allowable loads as follows:

3	Distance measured								
4	to the nearest								
5	foot between the								
6	extremes of any Maximum weight in pounds								
7	group of 2 or	of an	y group o	of					
8	more consecutive	2 or	more cons	secutive	axles				
9	axles								
10	feet	2 axles	3 axles	4 axles	5 axles	6 axles			
11	4	34,000							
12	5	34,000							
13	6	34,000							
14	7	34,000							
15	8	38,000*	42,000						
16	9	39,000	42,500						
17	10	40,000	43,500						
18	11		44,000						
19	12		45,000	50,000					
20	13		45,500	50,500					
21	14		46,500	51,500					
22	15		47,000	52,000					
23	16		48,000	52,500	58,000				
24	17		48,500	53,500	58,500				
25	18		49,500	54,000	59,000				
26	19		50,000	54,500	60,000				
27	20		51,000	55,500	60,500	66,000			
28	21		51,500	56,000	61,000	66,500			
29	22		52,500	56,500	61,500	67 , 000			
30	23		53,000	57 , 500	62 , 500	68,000			
31	24		54,000	58,000	63,000	68,500			
32	25		54,500	58,500	63,500	69,000			
33	26		55,500	59,500	64,000	69,500			
34	27		56,000	60,000	65,000	70,000			
35	28		57,000	60,500	65,500	71,000			

1	29	57 , 500	61,500	66,000	71,500
2	30	58 , 500	62,000	66,500	72,000
3	31	59 , 000	62,500	67 , 500	72 , 500
4	32	60,000	63,500	68,000	73,000
5	33		64,000	68,500	74,000
6	34		64,500	69,000	74,500
7	35		65 , 500	70,000	75 , 000
8	36		66,000	70,500	75 , 500
9	37		66,500	71,000	76,000
10	38		67 , 500	72,000	77,000
11	39		68,000	72,500	77,500
12	40		68,500	73,000	78,000
13	41		69,500	73 , 500	78 , 500
14	42		70,000	74,000	79,000
15	43		70,500	75,000	80,000
16	44		71,500	75 , 500	
17	45		72,000	76,000	
18	46		72,500	76,500	
19	47		73,500	77,500	
20	48		74,000	78,000	
21	49		74,500	78,500	
22	50		75 , 500	79,000	
23	51		76,000	80,000	
24	52		76,500		
25	53		77,500		
26	54		78,000		
27	55		78 , 500		
28	56		79,500		
29	57		80,000		
30	*If the distance between	2 axles is 9	6 inches	or less	, the 2
21	arriag and tandom arriag as	ad the marrim	·m +o+ol	rroight :	marr not

SB2343

31

32

33

34

35

36

- 9 - LRB093 20251 DRH 46017 b

axles are tandem axles and the maximum total weight may not exceed 34,000 pounds, notwithstanding the higher limit resulting from the application of the formula.

Vehicles not in a combination having more than 4 axles may not exceed the weight in the table in this subsection (f) for 4 axles measured between the extreme axles of the vehicle.

Vehicles in a combination having more than 6 axles may not exceed the weight in the table in this subsection (f) for 6 axles measured between the extreme axles of the combination.

Local authorities, with respect to streets and highways under their jurisdiction, without additional fees, may also by ordinance or resolution allow the weight limitations of this subsection, provided the maximum gross weight on any one axle shall not exceed 20,000 pounds and the maximum total weight on any tandem axle shall not exceed 34,000 pounds, on designated highways when appropriate regulatory signs giving notice are erected upon the street or highway or portion of any street or highway affected by the ordinance or resolution.

The following are exceptions to the above formula:

- (1) Two consecutive sets of tandem axles may carry a total weight of 34,000 pounds each if the overall distance between the first and last axles of the consecutive sets of tandem axles is 36 feet or more.
- (2) Vehicles for which a different limit is established and posted in accordance with Section 15-316 of this Code.
- (3) Vehicles for which the Department of Transportation and local authorities issue overweight permits under authority of Section 15-301 of this Code. These vehicles are not subject to the bridge formula.
- (4) Tow trucks subject to the conditions provided in subsection (d) may not exceed 24,000 pounds on a single rear axle or 44,000 pounds on a tandem rear axle.
- (5) A tandem axle on a 3-axle truck registered as a Special Hauling Vehicle, manufactured prior to or in the model year of 2014, and registered in Illinois prior to January 1, 2015, with a distance between 2 axles in a series greater than 72 inches but not more than 96 inches may not exceed a total weight of 36,000 pounds and neither axle of the series may exceed 18,000 pounds.
- (6) A truck not in combination, equipped with a self compactor or an industrial roll-off hoist and roll-off container, used exclusively for garbage or refuse

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

operations, may, when laden, transmit upon the road surface, except when on part of the National System of Interstate and Defense Highways, the following maximum weights: 22,000 pounds on a single axle; 40,000 pounds on a tandem axle; 36,000 pounds gross weight on a 2-axle vehicle; 54,000 pounds gross weight on a 3-axle vehicle. This vehicle is not subject to the bridge formula.

(7) Combinations of vehicles, registered as Special Hauling Vehicles that include a semitrailer manufactured prior to or in the model year of 2014, and registered in Illinois prior to January 1, 2015, having 5 axles with a distance of 42 feet or less between extreme axles, may not exceed the following maximum weights: 18,000 pounds on a single axle; 32,000 pounds on a tandem axle; and 72,000 pounds gross weight. This combination of vehicles is not subject to the bridge formula. For all those combinations of vehicles that include a semitrailer manufactured after the effective date of this amendatory Act of the 92nd General Assembly, the overall distance between the first and last axles of the 2 sets of tandems must be 18 feet 6 inches or more. Any combination of vehicles that has had its cargo container replaced in its entirety after December 31, 2014 may not exceed the weights allowed by the bridge formula.

No vehicle or combination of vehicles equipped with other than pneumatic tires may be operated, unladen or with load, upon the highways of this State when the gross weight on the road surface through any wheel exceeds 800 pounds per inch width of tire tread or when the gross weight on the road surface through any axle exceeds 16,000 pounds.

- (f-1) A vehicle and load not exceeding 73,280 pounds is allowed access as follows:
 - (1) From any State designated highway onto any county, township, or municipal highway for a distance of 5 highway miles for the purpose of loading and unloading, provided:
 - (A) The vehicle and load does not exceed 8 feet 6

1.3

- inches in width and 65 feet overall length.
- 2 (B) There is no sign prohibiting that access.
 - (C) The route is not being used as a thoroughfare between State designated highways.
 - (2) From any State designated highway onto any county or township highway for a distance of 5 highway miles, or any municipal highway for a distance of one highway mile for the purpose of food, fuel, repairs, and rest, provided:
 - (A) The vehicle and load does not exceed 8 feet 6 inches in width and 65 feet overall length.
 - (B) There is no sign prohibiting that access.
 - (C) The route is not being used as a thoroughfare between State designated highways.
 - (f-2) A vehicle and load greater than 73,280 pounds in weight but not exceeding 80,000 pounds is allowed access as follows:
 - (1) From a Class I highway onto any street or highway for a distance of one highway mile for the purpose of loading, unloading, food, fuel, repairs, and rest, provided there is no sign prohibiting that access.
 - (2) From a Class I, II, or III highway onto any State highway or any local designated highway for a distance of 5 highway miles for the purpose of loading, unloading, food, fuel, repairs, and rest.
 - Section 5-35 of the Illinois Administrative Procedure Act relating to procedures for rulemaking shall not apply to the designation of highways under this subsection.
 - (g) No person shall operate a vehicle or combination of vehicles over a bridge or other elevated structure constituting part of a highway with a gross weight that is greater than the maximum weight permitted by the Department, when the structure is sign posted as provided in this Section.
 - (h) The Department upon request from any local authority shall, or upon its own initiative may, conduct an investigation of any bridge or other elevated structure constituting a part of a highway, and if it finds that the structure cannot with

- safety to itself withstand the weight of vehicles otherwise permissible under this Code the Department shall determine and declare the maximum weight of vehicles that the structures can withstand, and shall cause or permit suitable signs stating maximum weight to be erected and maintained before each end of the structure. No person shall operate a vehicle or combination of vehicles over any structure with a gross weight that is
- 9 (i) Upon the trial of any person charged with a violation 10 of subsections (g) or (h) of this Section, proof of the 11 determination of the maximum allowable weight by the Department 12 and the existence of the signs, constitutes conclusive evidence 13 of the maximum weight that can be maintained with safety to the 14 bridge or structure.
- 15 (Source: P.A. 92-417, eff. 1-1-02; 93-177, eff. 7-11-03; 93-186, eff. 1-1-04; revised 8-12-03.)
- 17 (625 ILCS 5/15-201) (from Ch. 95 1/2, par. 15-201)

greater than the posted maximum weight.

- Sec. 15-201. Vehicles exceeding prescribed weight limits Preventing use of highway by.
- The Department of State Police is directed to institute and maintain a <u>non-discriminatory</u> program designed to prevent the use of public highways by vehicles which exceed the maximum weights allowed by Section 15-111 of this Act or which exceeds the maximum weights allowed as evidenced by the license plates attached to such vehicle and which license is required by this Act.
- 27 (Source: P.A. 84-25.)
- 28 (625 ILCS 5/15-202) (from Ch. 95 1/2, par. 15-202)
- Sec. 15-202. Enforcement.
- 30 <u>(a)</u> Such program shall make provision for an intensive <u>yet</u>
 31 <u>non-discriminatory</u> campaign by the State Police to apprehend
 32 any violators of the acts above mentioned, and at all times to
 33 maintain a vigilant watch for possible violators of such acts.
- 34 The State Police are prohibited, however, from routinely

4

5

6

7

9

1	stopping	and	d weighir	ng v	vehicles	transporting	а	particular
0	111					, ,	7	
/	COMMODIFV	$\circ r$	Wehicles	ın a	narticiila	ar geographic		ation

- (b) The Department of State Police shall provide training and continuing education to State Police officers concerning the prohibition on routinely stopping and weighing vehicles on the basis of the type of commodity the vehicle is transporting.

 This training and continuing education shall include, but not be limited to, an emphasis that the primary goal is equal and uniform enforcement of the State's weight limit laws.
- 10 (Source: P.A. 77-506.)
- 11 (625 ILCS 5/15-202.1 new)
- 12 <u>Sec. 15-202.1. Statistical study of vehicles which exceed</u>
 13 maximum weight limits.
- (a) Beginning January 1, 2005 and through December 31,

 2005, whenever a State Police officer issues a citation for an

 alleged violation of the maximum weight limits of this Code,
- 17 the officer shall record at least the following:
- 18 <u>(1) the make and year of the vehicle stopped;</u>
- 19 <u>(2) the date and time of the stop;</u>
- 20 (3) the county and location within the county of the 21 stop;
- 22 (4) the type of commodity being transported, with 23 emphasis on whether or not the commodity is an agricultural 24 commodity; and
- 25 (5) the weight of the vehicle and the amount, if any, 26 by which that weight exceeds the permitted weight.
- (b) The Department of State Police shall, by February 1, 27 2006, compile the data described in subsection (a). The 28 Department of State Police, in cooperation with the Illinois 29 30 Department of Agriculture, shall, by March 15, 2006, analyze the data and submit a report of the findings to the General 31 32 Assembly. In analyzing the data collected for the report, the analyzing entity shall scrutinize the data for evidence of 33 statistically significant aberrations with regard to any 34 disparity between the proportion of citations issued to the 35

- 1 <u>operators of vehicles transporting agricultural commodities</u>
- 2 and the proportion of citations issued to vehicles transporting
- 3 <u>non-agricultural commodities.</u>
- 4 Section 99. Effective date. This Act takes effect upon
- 5 becoming law.